

Okrugle cijevi Round tubes



Teorijska težina u Kg po linearnom metru. Theoretical weight in Kg per linear meter

Promjer Diameter (mm)	DN	Promjer Diameter PLIN; GAS	Debljina u mm; Thickness in mm																		
			0,4	0,5	0,6	0,8	1	1,2	1,5	1,6	2	2,3	2,5	2,6	3	3,2	3,6	4	5	6	
2			-	0,019	0,021	0,024	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2,5			-	0,025	0,029	0,034	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
3			-	0,032	0,036	0,044	0,050	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4			-	0,045	0,050	0,065	0,075	-	-	-	-	-	-	-	-	-	-	-	-	-	-
5			-	0,060	0,065	0,085	0,100	-	-	-	-	-	-	-	-	-	-	-	-	-	-
6			0,053	0,069	0,081	0,104	0,125	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7			-	0,085	0,095	0,125	0,150	0,175	0,210	-	-	-	-	-	-	-	-	-	-	-	-
7,5			0,710	0,090	0,105	0,135	0,165	0,190	0,225	-	-	-	-	-	-	-	-	-	-	-	-
8			0,076	0,094	0,111	0,144	0,175	0,204	0,244	-	-	-	-	-	-	-	-	-	-	-	-
9			-	0,110	0,125	0,165	0,200	0,220	0,285	-	-	-	-	-	-	-	-	-	-	-	-
9,5			0,910	0,115	0,135	0,175	0,215	0,250	0,300	-	-	-	-	-	-	-	-	-	-	-	-
10	6	1/8"	0,096	0,119	0,141	0,184	0,225	0,264	0,319	-	-	-	-	-	-	-	-	-	-	-	-
12			0,116	0,147	0,171	0,224	0,275	0,325	0,394	0,428	0,501	-	-	-	-	-	-	-	-	-	-
13			0,126	0,157	0,186	0,244	0,300	0,355	0,432	0,469	0,551	-	-	-	-	-	-	-	-	-	-
14	8	1/4"	0,136	0,169	0,201	0,264	0,326	0,385	0,470	0,510	0,601	-	-	-	-	-	-	-	-	-	-
15			0,146	0,182	0,216	0,284	0,351	0,415	0,507	0,552	0,651	-	-	-	-	-	-	-	-	-	-
16			0,156	0,194	0,231	0,304	0,376	0,445	0,545	0,577	0,701	-	-	-	-	-	-	-	-	-	-
17,2	10	3/8"	-	-	-	0,329	0,406	0,481	0,590	0,625	0,761	0,858	-	-	-	-	-	-	-	-	-
18			-	-	-	0,345	0,426	0,505	0,620	0,657	0,801	-	-	-	-	-	-	-	-	-	-
19,05			-	-	-	0,366	0,452	0,536	0,659	0,699	0,854	-	-	-	-	-	-	-	-	-	-
20			-	0,250	-	0,385	0,476	0,565	0,695	0,737	0,901	-	1,095	-	1,277	-	-	-	-	-	-
21,3	15	1/2"	-	-	-	0,411	0,508	0,604	0,744	0,789	0,967	1,094	1,177	1,217	1,380	-	-	-	-	-	-
22			-	-	-	0,425	0,526	0,625	0,770	0,817	1,002	-	-	-	-	-	-	-	-	-	-
24			-	-	-	0,465	0,576	0,685	0,845	0,897	1,102	-	-	-	-	-	-	-	-	-	-
25			-	-	-	0,485	0,601	0,715	0,883	0,937	1,152	1,307	1,409	1,458	1,652	-	-	-	-	-	-
25,4			-	-	-	0,493	0,611	0,727	0,898	0,954	1,172	1,330	1,434	1,484	1,682	-	-	-	-	-	-
26,9	20	3/4"	-	-	-	0,523	0,649	0,772	0,954	1,014	1,247	1,417	1,527	1,582	1,795	-	-	-	-	-	-
28			-	-	-	0,545	0,676	0,805	0,995	1,058	1,302	1,480	1,596	1,654	1,878	-	-	-	-	-	-
30			-	-	-	0,585	0,726	0,865	1,070	1,138	1,402	1,595	1,722	1,784	2,028	-	-	-	-	-	-
32			-	-	-	0,625	0,776	0,925	1,146	1,218	1,502	1,710	1,847	1,914	2,178	-	-	-	-	-	-
33,7	25	1"	-	-	-	0,659	0,819	0,977	1,209	1,286	1,588	1,808	1,953	2,025	2,306	2,444	-	-	-	-	-
34			-	-	-	0,665	0,826	0,986	1,221	1,298	1,603	1,826	1,972	2,044	2,329	2,468	-	-	-	-	-
35			-	-	-	0,685	0,851	1,016	1,258	1,338	1,653	1,883	2,035	2,109	2,404	2,548	-	-	-	-	-
38			-	-	-	0,745	0,926	1,106	1,371	1,458	1,803	2,056	2,222	2,305	2,629	2,788	-	-	-	-	-
40			-	-	-	0,785	0,977	1,166	1,446	1,538	1,903	2,171	2,348	2,435	2,779	2,949	-	-	-	-	-
42			-	-	-	0,825	1,027	1,226	1,521	1,619	2,003	2,286	2,473	2,565	2,930	3,109	-	-	-	-	-
42,4	32	1.1/4"	-	-	-	0,833	1,037	1,238	1,536	1,635	2,023	2,309	2,498	2,591	2,960	3,141	3,498	3,847	-	-	-
44,5			-	-	-	0,875	1,089	1,301	1,615	1,719	2,128	2,430	2,629	2,728	3,117	3,309	3,687	-	-	-	-
45			-	-	-	0,885	1,102	1,316	1,634	1,739	2,153	2,459	2,661	2,760	3,155	3,349	3,732	-	-	-	-
48,3	40	1.1/2"	-	-	-	0,952	1,184	1,415	1,758	1,871	2,319	2,649	2,867	2,975	3,403	3,614	4,029	4,437	-	-	-
50			-	-	-	0,986	1,227	1,466	1,822	1,939	2,404	2,747	2,974	3,086	3,531	3,750	4,183	-	-	-	-
50,8			-	-	-	1,002	1,247	1,490	1,852	1,971	2,444	2,793	3,024	3,138	3,591	3,814	4,255	-	-	-	-
51			-	-	-	-	1,252	1,496	1,859	1,979	2,454	2,805	3,036	3,151	3,606	3,830	4,273	-	-	-	-
52			-	-	-	-	1,277	1,526	1,897	2,019	2,504	2,862	3,099	3,216	3,681	3,910	4,363	-	-	-	-
53			-	-	-	-	1,302	1,556	1,934	2,059	2,554	2,920	3,161	3,281	3,756	3,990	4,453	-	-	-	-
54			-	-	-	-	1,327	1,587	1,972	2,099	2,604	2,978	3,224	3,346	3,831	4,071	4,543	-	-	-	-
57			-	-	-	-	1,402	1,677	2,085	2,220	2,754	3,150	3,412	3,542	4,056	4,311	4,814	-	-	-	-
60,3	50	2"	-	-	-	-	1,485	1,776	2,209	2,352	2,920	3,340	3,618	3,757	4,304	4,575	5,111	5,640	-	-	-
63,5			-	-	-	-	-	1,872	2,329	2,480	3,080	3,525	3,819	3,965	4,545	4,832	5,400	5,960	-	-	-



Teorijska težina u Kg po linearnom metru. Theoretical weight in Kg per linear meter

Promjer Diameter (mm)	DN	Promjer Diameter PLIN; GAS	Debljina u mm; Thickness in mm																			
			0,4	0,5	0,6	0,8	1	1,2	1,5	1,6	2	2,3	2,5	2,6	3	3,2	3,6	4	5	6		
70			-	-	-	-	-	-	2,067	2,573	2,740	3,405	3,899	4,226	4,388	5,033	5,353	5,986	6,611	-	-	-
73			-	-	-	-	-	-	2,157	2,686	2,861	3,556	4,072	4,413	4,583	5,258	5,593	6,256	-	-	-	-
76,1	65	2.1/2"	-	-	-	-	-	-	2,251	2,802	2,985	3,711	4,250	4,607	4,785	5,491	5,841	6,535	7,222	-	-	-
80			-	-	-	-	-	-	2,368	2,948	3,141	3,906	4,475	4,852	5,039	5,784	6,154	6,887	7,612	-	-	-
83			-	-	-	-	-	-	2,458	3,061	3,261	4,056	4,648	5,039	5,234	6,010	6,394	7,157	7,913	-	-	-
84			-	-	-	-	-	-	2,488	3,099	3,301	4,107	4,705	5,102	5,299	6,085	6,474	7,248	8,013	-	-	-
85			-	-	-	-	-	-	2,518	3,136	3,341	4,157	4,763	5,165	5,365	6,160	6,554	7,338	8,113	-	-	-
88,9	80	3"	-	-	-	-	-	-	2,635	3,283	3,498	4,352	4,987	5,409	5,618	6,453	6,867	7,689	8,504	-	-	-
101,6	90	3.1/2"	-	-	-	-	-	-	-	3,760	4,006	4,988	5,719	6,204	6,445	7,407	7,885	8,834	9,776	-	-	-
104			-	-	-	-	-	-	3,850	4,103	5,108	5,857	6,354	6,602	7,587	8,077	9,050	10,016	-	-	-	-
108			-	-	-	-	-	-	4,000	4,263	5,308	6,087	6,604	6,862	7,888	8,397	9,411	10,417	-	-	-	-
114,3	100	4"	-	-	-	-	-	-	-	4,237	4,515	5,624	6,450	6,999	7,272	8,361	8,902	9,979	11,048	-	-	-
127			-	-	-	-	-	-	4,714	5,024	6,260	7,182	7,794	8,099	9,315	9,920	11,124	12,320	15,274	-	-	-
128			-	-	-	-	-	-	4,751	5,064	6,310	7,239	7,856	8,164	9,390	10,000	11,214	12,420	15,400	-	-	-
129			-	-	-	-	-	-	-	4,789	5,104	6,360	7,297	7,919	8,229	9,465	10,080	11,304	12,520	15,525	-	-
139,7	125	5"	-	-	-	-	-	-	-	5,191	5,533	6,896	7,913	8,589	8,926	10,269	10,937	12,269	13,592	16,864	20,087	-
153			-	-	-	-	-	-	-	5,690	6,066	7,562	8,679	9,421	9,792	11,268	12,003	13,468	14,924	18,530	22,085	-
154			-	-	-	-	-	-	5,728	6,106	7,612	8,737	9,484	9,857	11,343	12,083	13,558	15,024	18,655	22,236	-	-
156			-	-	-	-	-	-	5,803	6,186	7,712	8,852	9,609	9,987	11,493	12,244	13,738	15,224	18,905	22,536	-	-
159			-	-	-	-	-	-	5,916	6,306	7,863	9,025	9,797	10,182	11,719	12,484	14,008	15,525	19,281	22,897	-	-
168,3	150	6"	-	-	-	-	-	-	6,265	6,679	8,328	9,560	10,379	10,788	12,417	13,229	14,847	16,456	20,445	24,384	-	-
203			-	-	-	-	-	-	-	-	-	10,066	11,559	12,551	13,047	15,024	16,010	17,975	19,932	24,790	29,597	-
204			-	-	-	-	-	-	-	-	-	10,116	11,616	12,614	13,112	15,099	16,090	18,065	20,032	24,915	29,748	-
205			-	-	-	-	-	-	-	-	-	10,166	11,674	12,677	13,177	15,174	16,170	18,155	20,132	25,040	29,898	-
206			-	-	-	-	-	-	-	-	-	10,216	11,731	12,739	13,242	15,249	16,250	18,245	20,232	25,165	30,048	-
219,1	200	8"	-	-	-	-	-	-	-	-	-	10,872	12,486	13,559	14,095	16,233	17,300	19,426	21,544	26,805	32,016	-
253			-	-	-	-	-	-	-	-	-	12,570	14,438	15,681	16,302	18,780	20,016	22,482	24,940	31,050	37,109	-
254			-	-	-	-	-	-	-	-	-	12,620	14,496	15,744	16,367	18,855	20,096	22,572	25,040	31,175	37,260	-
255			-	-	-	-	-	-	-	-	-	12,670	14,553	15,807	16,432	18,930	20,176	22,662	25,140	31,300	37,410	-
256			-	-	-	-	-	-	-	-	-	12,720	14,611	15,869	16,497	19,005	20,256	22,752	25,240	31,425	37,560	-
273	250	10"	-	-	-	-	-	-	-	-	-	13,572	15,590	16,933	17,604	20,282	21,619	24,285	26,943	33,554	40,114	-
304			-	-	-	-	-	-	-	-	-	15,124	17,376	18,874	19,622	22,611	24,103	27,079	30,048	37,435	44,772	-
305			-	-	-	-	-	-	-	-	-	15,174	17,433	18,937	19,687	22,686	24,183	27,169	30,148	37,560	44,922	-
306			-	-	-	-	-	-	-	-	-	15,224	17,491	18,999	19,753	22,761	24,263	27,260	30,248	37,685	45,072	-
323,9	300	12"	-	-	-	-	-	-	-	-	-	16,121	18,522	20,120	20,918	24,106	25,697	28,873	32,041	39,926	47,761	-
353			-	-	-	-	-	-	-	-	-	17,578	20,198	21,941	22,812	26,292	28,029	31,496	34,956	43,570	52,133	-
354			-	-	-	-	-	-	-	-	-	17,628	20,255	22,004	22,878	26,367	28,109	31,586	35,056	43,695	52,284	-
355,6	350	14"	-	-	-	-	-	-	-	-	-	17,708	20,347	22,104	22,982	26,487	28,237	31,731	35,216	43,895	52,524	-
406,4	400	16"	-	-	-	-	-	-	-	-	-	20,252	23,273	25,284	26,289	30,303	32,308	36,310	40,304	50,255	60,156	-
457	450	18"	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	45,370	56,590	67,760	-
506			-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50,280	62,730	75,120	-
508	500	20"	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50,480	63,980	75,420	-
609,6	600	24"	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	60,660	75,700	90,690	-
711			-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	70,810	88,390	105,920	-

Artikl; Item: **TEL** (šavna cijev, lasersko zavarivanje Laser - TIG; welded tube, laser welding Laser - TIG)
 Artikl; Item: **THF** (šavna cijev, visokofrekventno zavarivanje; welded tube, high frequency welding)
 Artikl; Item: **TER** (šavna cijev, lasersko zavarivanje Laser – TIG, žarena max Ø219; welded tube, laser welding Laser - TIG, annealed max Ø 219)
 Artikl; Item: **TLN** (šavna cijev, lasersko zavarivanje Laser - TIG, polirane; welded tube, laser welding Laser - TIG, ship polishing)
 Artikl; Item: **TIE** (šavna cijev, za prehrambenu industriju, lasersko zavarivanje Laser - TIG, vanjsko/unutarnje poliranje; welded tube, for food industry, laser welding Laser - TIG, internal/external polishing)
 Artikl; Item: **TEE** (šavna cijev, za prehrambenu industriju, lasersko zavarivanje Laser - TIG, vanjsko poliranje; welded tube, for food industry, laser welding Laser - TIG, external polishing)
 Artikl; Item: **THFS** (šavna satinirana cijev, visokofrekventno zavarivanje; welded Scotch brite tube, high frequency welding)
 Artikl; Item: **TELS** (šavna satinirana cijev, lasersko zavarivanje Laser - TIG; welded Scotch brite tube, laser welding Laser – TIG)

Okrugle cijevi od Ø 2,5 do Ø 771 mm.
 Završna obrada: dekapirano, četkano ili satinirano.
 Komercijalna dužina 6 m.
 Round tubes from Ø 2.5 to Ø 771 mm.
 The final processing: pickled, brushed or scotch brite.
 Commercial length is 6 m.

Standardne dimenzije su podebljane crnom bojom.
Standard dimensions are in bold.